



PT-70
ROTARY EVAPORATOR RAPIDVAP

PT-71
ROTARY EVAPORATOR RAPIDVAP

PT-70 & PT-71

Rotary evaporators are used for:

- **Solvent Removal:** Efficiently evaporating and recovering solvents from samples in chemical and pharmaceutical industries.
- **Purification and Concentration:** Concentrating solutions and purifying compounds by removing excess solvents.
- **Sample Preparation:** Preparing samples for further analysis by removing solvents under reduced pressure.
- **Recrystallization:** Purifying solid compounds by dissolving them in a solvent and then evaporating the solvent to form crystals.
- **Extraction of Natural Products:** Isolating bioactive compounds from plant materials and other natural sources.
- **Food and Beverage Industry:** Concentrating flavors, fragrances, and other ingredients for product development.

PT-70 & PT-71 ROTARY EVAPORATOR RAPIDVAP

(HSN-84198990)

MODEL NUMBER	PT-70	PT-71
RATES	73950/-	81950/-
GLASSWARE		
Condenser Type	Vertical	Vertical
Cooling Surface	1500 cm2	1500 cm2
Evaporating Flask**	100 ml to 2000 ml	100 ml to 2000 ml
Receiving Flask	Max 1000 ml	Max 1000 ml
GENERAL		
Motor Principle	DC	DC
Speed Range	20-200 rpm	20-200 rpm
RPM Display	-	-
Lift	Manual	Manual
Stroke	100 mm	100 mm
Lift Speed	-	-
Voltage	220-240 V	220-240 V
Frequency	50 Hz	50 Hz
WATER BATH		
Temperature Controller	Thermostat	Digital (PID)
Heating Temperature Range	Ambient + 5°C - 95 °C	Ambient + 5°C - 180 °C
Heat Output	1250 W	1250 W
Temperature Uniformity	±1 °C	±1 °C
Filling Volume Max.	3.5 L	3.5 L
Inner Body	Stainless Steel 304 Grade	Stainless Steel 304 Grade
Outer Body	Aluminium Powder Coated	Aluminium Powder Coated
SIZE & WEIGHT		
Dimensions (L x W x H)	660 x 530 x 860 mm	710 x 530 x 860 mm
Weight	24 kg	25 kg
OPERATING CONDITIONS		
Permissible ambient temperature	5 - 40 °C	5 - 40 °C
Permissible relative humidity	80 %	80 %
IP Rating	IP 20	IP 20

**Evaporating flask supplied with unit is 800 mL, rest are optional.